



Hinged pin wrench straight, largest \varnothing / pin nominal \varnothing : 40/4mm



Description

Version:

Special steel, drive head ground, annealed and burnished.

With fixed pins.

Application:

For twin hole nuts.

Note:

Pin \varnothing = pin nominal \varnothing - 0.1 mm; tolerance field h12.

Technical description

largest \varnothing	40 mm
Pin nominal \varnothing	4 mm
overall length	150 mm
Pin spacing adjustable a	18 - 40 mm
Type	764C
Manufacturer's designation	764
Type of product	Pin spanner



Hinged pin wrench straight, largest \varnothing / pin nominal \varnothing : 80/4mm



Description

Version:

Special steel, drive head ground, annealed and burnished.

With fixed pins.

Application:

For twin hole nuts.

Note:

Pin \varnothing = pin nominal \varnothing - 0.1 mm; tolerance field h12.

Technical description

largest \varnothing	80 mm
Pin spacing adjustable a	40 - 80 mm
Pin nominal \varnothing	4 mm
overall length	220 mm
Type	764C
Manufacturer's designation	764
Type of product	Pin spanner



Hinged pin wrench straight, largest \varnothing / pin nominal \varnothing : 80/6mm



Description

Version:

Special steel, drive head ground, annealed and burnished.

With fixed pins.

Application:

For twin hole nuts.

Note:

Pin \varnothing = pin nominal \varnothing - 0.1 mm; tolerance field h12.

Technical description

Pin nominal \varnothing	6 mm
Pin spacing adjustable a	40 - 80 mm
overall length	220 mm
largest \varnothing	80 mm
Type	764C
Manufacturer's designation	764
Type of product	Pin spanner



Hinged pin wrench straight, largest \varnothing / pin nominal \varnothing : 125/6mm



Description

Version:

Special steel, drive head ground, annealed and burnished.

With fixed pins.

Application:

For twin hole nuts.

Note:

Pin \varnothing = pin nominal \varnothing - 0.1 mm; tolerance field h12.

Technical description

largest \varnothing	125 mm
Pin nominal \varnothing	6 mm
Pin spacing adjustable a	80 - 125 mm
overall length	295 mm
Type	764C
Manufacturer's designation	764
Type of product	Pin spanner



Hinged pin wrench straight, largest \varnothing / pin nominal \varnothing : 125/8mm



Description

Version:

Special steel, drive head ground, annealed and burnished.

With fixed pins.

Application:

For twin hole nuts.

Note:

Pin \varnothing = pin nominal \varnothing - 0.1 mm; tolerance field h12.

Technical description

overall length	295 mm
Pin spacing adjustable a	80 - 125 mm
largest \varnothing	125 mm
Pin nominal \varnothing	8 mm
Type	764C
Manufacturer's designation	764
Type of product	Pin spanner